

## Signal-/telecommunications cable Jobsignal YY-ST



**Application** : Signal and control cable for use in intercom, telephone and security appliances.

**TECHNICAL DATA** : TYPE YY-ST

Standards : KEMA K 102-314

**Remarks** : Colour code according to NEN1597. Drain wire 0.8mm underneath foil. Outer jacket PVCmb.

Conductor category	: Class 1 = solid
Conductor material	: Cu, bare
Stranding	: Bundle
Stranding element	: Pairs
Core insulation	: PVC
Core identification	: Colour
Screen over stranding element	: None
Screen over stranding	: Foil
Longitudinal water blocking	: No
Radial water blocking	: No
Protective sheath	: No
Armouring	: No
Material outer sheath	: PVC
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Circuit integrity	: No
Permitted cable outer temperature, fixed	: -20°C to 70°C
Outdoor use permitted	: No

ProductNr	Dimension	Colour outer sheath	Outer diameter approx. (mm)
0158703	1 x 2 x 0,8	Blue	5.2
0158602	1 x 2 x 0,8	Grey	5.2
0158702	1 x 2 x 0,8	Red	5.2
0158705	2 x 2 x 0,8	Blue	6.8
0158604	2 x 2 x 0,8	Grey	6.8
0158704	2 x 2 x 0,8	Red	6.8
0158606	3 x 2 x 0,8	Grey	7.5
0158709	4 x 2 x 0,8	Blue	8.2
0158608	4 x 2 x 0,8	Grey	8.2
0158610	5 x 2 x 0,8	Grey	9
0158612	6 x 2 x 0,8	Grey	9.6
0158616	8 x 2 x 0,8	Grey	10.2
0158624	12 x 2 x 0,8	Grey	12.3