

## Control cable Armaflex T



<b>Application</b>	<b>: For flexible use in lighting fixtures. This type has a steel wire for strain relief (max. weight 80 kg).</b>
<b>TECHNICAL DATA</b>	<b>: 0100203</b>
<b>Remarks</b>	<b>: Cores colour coded: 1 core transparent, 1 core with brown identification wire, 1 core with blue identification wire</b>
Dimension	: 3 x 1,5
Conductor category	: Class 5 = flexible
Stranding element	: No
Conductor material	: Cu, tinned
Core insulation	: Other
Core identification	: Colour
Protective conductor	: No
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: None
Material outer sheath	: PVC
Colour outer sheath	: Transparent
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: No
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Outer diameter approx.	: 7.5mm
Permitted cable outer temperature, in movement	: -5°C to 70°C
Permitted cable outer temperature, fixed	: -30°C to 80°C
Nominal voltage U	: 300V
Core protecton	: No