

Control cable Armaflex



Application : For flexible use in lighting fixtures. Available in standard version (Armaflex) or in a version with a steel wire (Armaflex-T) for strain relief (max. weight 80 kg).

TECHNICAL DATA : Armaflex

Remarks : Cores colour coded: 1 core transparent, 1 core with brown identification wire, 1 core with blue identification wire

Conductor category	: Class 5 = flexible
Stranding element	: No
Conductor material	: Cu, tinned
Core insulation	: Other
Core identification	: Colour
Protective conductor	: No
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: None
Material outer sheath	: PVC
Colour outer sheath	: Transparent
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: No
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Permitted cable outer temperature, in movement	: -5°C to 70°C
Permitted cable outer temperature, fixed	: -30°C to 80°C
Nominal voltage U	: 300V
Core protecton	: No

ProductNr	Dimension	Outer diameter approx. (mm)
-----------	-----------	-----------------------------

ProductNr	Dimension	Outer diameter approx. (mm)
0100199	3 x 0,75	6.1
0100200	3 x 0,75	6.1
0100202	3 x 1,5	7
0100205	3 x 1,5	7