

Data and communication cable Alarm Alarmkabel pvc Dca



Application : Special, halogen free combi cable for use in alarm and security systems.

TECHNICAL DATA : TYPE Alarmkabel pvc Dca

Standards	: CPR
	: 0.22mm ²
Stranding element	: Pairs
Conductor material	: Copper, bare
Conductor category	: Class 2 = stranded
Core insulation material	: Polyvinyl chloride (PVC)
Core identification	: Colour
Stranding	: Bundle
Material outer sheath	: Polyvinyl chloride (PVC)
Screen over stranding element	: None
Screen over stranding	: Foil
Halogen free (acc. IEC 60754-2)	: No
Longitudinal water blocking	: No
Halogen free (acc. EN 60754-1/2)	: No
Radial water blocking	: No
Low smoke (acc. IEC 61034-2)	: No
Protective sheath	: No
Low smoke (acc. BS EN 61034-2)	: No
Armouring	: No
Oil resistant (acc. IEC 60811-404)	: No
Colour outer sheath	: White
Permitted cable outer temperature during assembling/handling	: -5°C to 90°C
Permitted cable outer temperature after assembling without vibration	: -30°C to 90°C
Flame retardant	: No
Smoke development class according to EN 13501-6	: s3
Circuit integrity	: No
Euro class acidity according to EN 13501-6	: a3
Outdoor use permitted	: No
Reaction-to-fire class according to EN 13501-6	: Dca
Euro class flaming droplets/particles according to EN 13501-6	: d2
UV resistant	: No
Armouring/reinforcement	: None
Conductor surface	: Bare



JOBARCO

Longitudinal water blocking cable : No
Radial water blocking cable : No
Oil resistant (acc. EN 60811-404) : No
: Round
: No
: No
: No
: Yes

ProductNr	Dimension		Number of stranding elements	Outer diameter approx. (mm)
0155180	2 x 0.5 + 4 x 0.22	4	3	5.6
0155182	2 x 0.5 + 6 x 0.22	6	4	5.8
0155184	2 x 0.5 + 8 x 0.22	8	5	6.6