



JOBARCO

Power cable < 1 kV, for flexible applications Camerakabel CAM-CC



Application	: Flexible combi cable for use in security systems, such as camera surveillance systems.
TECHNICAL DATA	: TYPE CAM-CC
Remarks	: 2 flexible cores + 1 x coax 75 Ohm
Conductor material	: Copper, bare
	: 1
Stranding element	: No
Conductor category	: Class 5 = flexible
Core insulation material	: Copolymer, thermoplastic
Protective conductor	: No
Core identification	: Colour
Suspension element	: None
Inner sheath	: No
Screen over stranding element	: None
Screen	: No
Screen over stranding	: None
Model	: Round
Colour outer sheath	: Black
Material outer sheath	: Polyvinyl chloride (PVC)
Flame retardant	: In accordance with EN 60332-1-2
Torsion resistant	: No
Halogen free (acc. EN 60754-1/2)	: No
Oil resistant (acc. EN 60811-404)	: No
Low smoke (acc. BS EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Permitted cable outer temperature during assembling/handling	: -5°C to 70°C
Permitted cable outer temperature after assembling without vibration	: -30°C to 70°C
Max. conductor temperature	: 70°C
Nominal voltage U0	: 500V
Core protecton	: No
Nominal voltage U	: 500V
Conductor surface	: Bare
Specification core insulation	: Other
	: No
Specification material outer sheath	: Other
	: Round



Shape of conductor

: Round

ProductNr	Dimension	Outer diameter approx. (mm)	Bending radius (mm)
0100112	2 x 0.75 + 1 x 1.4	11	165
0100113	3 x 0.75 + 1 x 1.4	11.1	167
0100114	4 x 0.75 + 1 x 1.4	11.6	174