



JOBARCO

Power cable < 1 kV, for flexible applications Camerakabel CAM-CY



Application : Flexible combi cable for use in security systems, such as camera surveillance systems. Shielded with tinned copper braiding.

TECHNICAL DATA : 0100214

Remarks : 4 flexible cores + 1 x coax 75 Ohm

Dimension	: 4 x 0.75 + 1 x 1.4
Conductor material	: Copper, bare
	: 1
Stranding element	: No
Conductor category	: Class 5 = flexible
Core insulation material	: Copolymer, thermoplastic
Protective conductor	: No
Core identification	: Colour
Suspension element	: None
Inner sheath	: No
Screen over stranding element	: None
Screen	: Yes
Screen over stranding	: None
Model	: Round
Colour outer sheath	: Black
Material outer sheath	: Polyvinyl chloride (PVC)
Flame retardant	: In accordance with EN 60332-1-2
Torsion resistant	: No
Halogen free (acc. EN 60754-1/2)	: No
Oil resistant (acc. EN 60811-404)	: No
Low smoke (acc. BS EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Outer diameter approx.	: 12.1mm
Permitted cable outer temperature during assembling/handling	: -5°C to 70°C
Permitted cable outer temperature after assembling without vibration	: -30°C to 70°C
Max. conductor temperature	: 70°C
Bending radius	: 182mm
Nominal voltage U ₀	: 500V
Core protecton	: No
Nominal voltage U	: 500V
Conductor surface	: Bare



JOBARCO

Specification core insulation	: Other
	: No
Specification material outer sheath	: Other
	: Round
Shape of conductor	: Round