

## Control cable Camerakabel CAM-CY



<b>Application</b>	: Flexible combi cable for use in security systems, such as camera surveillance systems. Shielded with tinned copper braiding.
<b>TECHNICAL DATA</b>	: <b>0100214</b>
<b>Remarks</b>	: <b>4 flexible cores + 1 x coax 75 Ohm</b>
Dimension	: 4 x 0,75
Conductor category	: Class 5 = flexible
Stranding element	: No
Conductor material	: Cu, bare
Core insulation	: Copolymer, thermoplastic
Core identification	: Colour
Protective conductor	: No
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: None
Material outer sheath	: PVC
Colour outer sheath	: Black
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Outer diameter approx.	: 12.1mm
Permitted cable outer temperature, in movement	: -5°C to 70°C
Permitted cable outer temperature, fixed	: -30°C to 70°C
Nominal voltage U	: 500V
Bending radius	: 182mm
Core protecton	: No