

Data and communication cable Joblift Cat 6A



Application : Flexible shielded bus cable for TCP/IP -Fast Ethernet- cat. 61000 Mbit/s applications, max. 250 MHz. Especially suitable for use in elevators, cranes and other support systems. Cat6A according to IEC 61156-6.

TECHNICAL DATA : 0159990

Remarks : Due to the aramid fiber strain relief construction, this cable is suitable for suspension height of max. 100 meter.

Dimension	: 4 x 2 x AWG26
Stranding element	: Pairs
Conductor material	: Copper, bare
Conductor category	: Class 5 = flexible
Core insulation material	: Polyolefin
Core identification	: Colour
Material outer sheath	: Polyvinyl chloride (PVC)
Screen over stranding element	: Foil
Screen over stranding	: Braiding
Halogen free (acc. IEC 60754-2)	: No
Longitudinal water blocking	: No
Halogen free (acc. EN 60754-1/2)	: No
Radial water blocking	: No
Low smoke (acc. IEC 61034-2)	: No
Protective sheath	: No
Low smoke (acc. BS EN 61034-2)	: No
Armouring	: No
Oil resistant (acc. IEC 60811-404)	: No
Colour outer sheath	: Black
Permitted cable outer temperature during assembling/handling	: -10°C to 70°C
Permitted cable outer temperature after assembling without vibration	: -40°C to 80°C
Category	: 6A (IEC)
Flame retardant	: In accordance with EN 60332-3-24
Circuit integrity	: No
Bending radius	: 132mm
Number of stranding elements	: 4
Outer diameter approx.	: 8.8mm
Outdoor use permitted	: No
UV resistant	: No



JOBARCO

Armouring/reinforcement	: None
Conductor surface	: Bare
AWG size	: 26
	: No
Longitudinal water blocking cable	: No
Radial water blocking cable	: No
	: Round
Oil resistant (acc. EN 60811-404)	: No
Underground installation	: No
	: No
	: No
	: Yes
	: Yes