

## Data and communication cable Dataflex CKY



**Application** : Used as computer cable and in other data transmission systems. Flexible, twisted pairs, overall braiding.

**TECHNICAL DATA** : TYPE CKY

Stranding element	: Pairs
Conductor material	: Copper, bare
Conductor category	: Class 5 = flexible
Core insulation material	: Polyvinyl chloride (PVC)
Core identification	: Colour
Material outer sheath	: Polyvinyl chloride (PVC)
Screen over stranding element	: None
Screen over stranding	: Braiding
Halogen free (acc. IEC 60754-2)	: No
Longitudinal water blocking	: No
Halogen free (acc. EN 60754-1/2)	: No
Radial water blocking	: No
Low smoke (acc. IEC 61034-2)	: No
Protective sheath	: Polyvinyl chloride (PVC)
Low smoke (acc. BS EN 61034-2)	: No
Armouring	: No
Oil resistant (acc. IEC 60811-404)	: No
Permitted cable outer temperature during assembling/handling	: -5°C to 70°C
Permitted cable outer temperature after assembling without vibration	: -30°C to 70°C
Category	: Other
Flame retardant	: In accordance with EN 60332-1-2
Outdoor use permitted	: No
UV resistant	: No
Armouring/reinforcement	: None
Conductor surface	: Bare
	: No
Longitudinal water blocking cable	: No
Radial water blocking cable	: No
	: Round
Oil resistant (acc. EN 60811-404)	: No
Underground installation	: No
	: No
	: No
	: No
	: Yes



**JOBARCO**

: Yes



# JOBARCO

<b>ProductNr</b>	<b>Dimension</b>	<b>Colour outer sheath</b>	<b>Number of stranding elements</b>	<b>Outer diameter approx. (mm)</b>
0111109	8 x 2 x 0.25	Blue	8	9.3
0111206	6 x 2 x 0.5	Grey	6	11.7
0111208	7 x 2 x 0.5	Grey	7	12.9
0111217	16 x 2 x 0.5	Blue	16	17.6
0111220	20 x 2 x 0.5	Grey	20	18.9
0111434	4 x 2 x 0.75	Blue	4	11.3
0111409	8 x 2 x 0.75	Blue	8	14.6
0111428	16 x 2 x 0.75	Grey	16	18.9
0111435	25 x 2 x 0.75	Blue	25	23.3