

Control cable EQ-flex LIYYCY-JZ



Application : Flexible cable, copper braided. Protects against electromagnetic interference.

TECHNICAL DATA : TYPE LIYYCY-JZ

Remarks : Oil resistant according to EN 50290-2-22 (TM54).

Conductor category : Class 5 = flexible
 Stranding element : No
 Conductor material : Cu, bare
 Core insulation : PVC
 Core identification : Numbers
 Protective conductor : Yes
 Screen over stranding element : None
 Screen over stranding : Braiding
 Material outer sheath : PVC
 Halogen free (acc. EN 60754-1/2) : No
 Low smoke (acc. EN 61034-2) : No
 Low temperature resistant (acc. EN 60811-504+505+506) : No
 Oil resistant (acc. EN 60811-404) : Yes
 Permitted cable outer temperature, in movement : -5°C to 70°C
 Permitted cable outer temperature, fixed : -30°C to 70°C
 Core protecton : No
 Euro fire class acc. to EN 13501-6 : Eca

ProductNr	Dimension	Inner sheath	Colour outer sheath	Flame retardant	Outer diameter approx. (mm)	Nominal voltage U (V)
1095604	4 x 1,5	No	Other	No	9.7	300
1017620	18 x 1,5	Yes	Grey	In accordance with EN 60332-1-2	21	500