

Power cable < 1 kV, for flexible applications Flexellent SAN-C



Application	: Highly flexible, halogen free cable with high chemical resistance and a temperature range of -50° up to +110°C. Very suitable for the Food and Beverage industry: tested and approved by Ecolab for resistance to various aggressive cleaning products.
TECHNICAL DATA	: TYPE SAN-C
Remarks	: High resistance to UV- and ozon, solvents, hydrolysis, microbes and animal fats. Wear and tear resistant. resistant to sulphuric acid, battery acid, nitric acid and chlorine.
Conductor material	: Copper, tinned
Stranding element	: No
Conductor category	: Class 6 = very flexible
Core insulation material	: Copolymer, thermoplastic
Protective conductor	: Yes
Core identification	: Numbers
Suspension element	: None
Inner sheath	: No
Screen over stranding element	: None
Screen	: Yes
Screen over stranding	: Braiding
Model	: Round
Colour outer sheath	: Black
Material outer sheath	: Copolymer, thermoplastic
Flame retardant	: No
Halogen free (acc. EN 60754-1/2)	: Yes
Oil resistant (acc. EN 60811-404)	: Yes
Low smoke (acc. BS EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Permitted cable outer temperature during assembling/handling	: -40°C to 110°C
Permitted cable outer temperature after assembling without vibration	: -50°C to 110°C
Max. conductor temperature	: 110°C
Nominal voltage U ₀	: 300V
Core protecton	: No
Nominal voltage U	: 500V
Conductor surface	: Tinned
Specification core insulation	: Other
	: No



JOBARCO

Specification material outer sheath

: Other

: Round

Shape of conductor

: Round



JOBARCO

ProductNr	Dimension	Outer diameter approx. (mm)
0132604	4 x 1.5	9.4
0132607	7 x 1.5	12.2
0132612	12 x 1.5	14.7
0132704	4 x 2.5	11.7
0132804	4 x 4	13.2
0132904	4 x 6	16.4