

Signal-/telecommunications cable Jobsignal HH-ST mbzh



Application : Signal and control cable for use in intercom, telephone and security appliances.
Halogen free and low smoke.

TECHNICAL DATA : TYPE HH-ST mbzh

Standards : K165-5.

Remarks : Colour code according to NEN1597. Drain wire 0.8mm underneath foil.

Conductor category	: Class 1 = solid
Conductor material	: Cu, bare
Stranding	: Bundle
Stranding element	: Pairs
Core insulation	: Polyolefin
Core identification	: Colour
Screen over stranding element	: None
Screen over stranding	: Foil
Longitudinal water blocking	: No
Radial water blocking	: No
Protective sheath	: No
Armouring	: No
Material outer sheath	: Polyolefin
Halogen free (acc. EN 60754-1/2)	: Yes
Flame retardant	: In accordance with EN 60332-3-24
Low smoke (acc. EN 61034-2)	: Yes
Circuit integrity	: No
Permitted cable outer temperature, fixed	: -20°C to 70°C
Outdoor use permitted	: No

ProductNr	Dimension	Colour outer sheath	Outer diameter approx. (mm)
0155024	1 x 2 x 1	Red	5.7

ProductNr	Dimension	Colour outer sheath	Outer diameter approx. (mm)
0155025	1 x 2 x 1,5	Red	6.2
0155021	4 x 1 x 0,8	Red	6.5
0155006	3 x 2 x 0,8	Grey	7.1
0155008	4 x 2 x 0,8	Grey	7.7