

Data cable Highflex PRO CKY 2D



Application : Suitable for use in cable chain systems. The keen construction makes the cable extremely flexible and applicable in various continuously moving equipment. The cable has a diminutive bend radius which makes it possible to use it in small spaces.

TECHNICAL DATA : TYPE PRO CKY 2D

Remarks : Very good petrol and oil resistant. Sea water resistant. Halogen free. Colour jacket is petrolblue.

Stranding element : Pairs
 Conductor material : Cu, bare
 Conductor category : Class 6 = very flexible
 Core insulation : Polypropylene
 Core identification : Colour
 Screen over stranding element : None
 Screen over stranding : Braiding
 Material outer sheath : Other
 Colour outer sheath : Other
 Halogen free (acc. EN 60754-1/2) : Yes
 Flame retardant : No
 Low smoke (acc. EN 61034-2) : No
 Permitted cable outer temperature, in movement : -25°C to 90°C
 Permitted cable outer temperature, fixed : -40°C to 90°C

ProductNr	Dimension	Outer diameter approx. (mm)	Bending radius (mm)	Number of stranding elements
0169060	2 x 2 x 0,25	6.6	42	2
0169062	4 x 2 x 0,25	8	52	4
0169063	8 x 2 x 0,25	11	71	8