



JOBARCO

Power cable < 1 kV, for flexible applications Highflex PRO CY UL



Application	: Suitable for use in cable chain systems. The keen construction makes the cable extremely flexible and applicable in various continuous moving equipment. The cable has a diminutive bend radius which makes it possible to use it in minuscule spaces. With UL approval.
TECHNICAL DATA	: 0169207
Standards	: UL 21530
Remarks	: Very good petrol and oil resistant. Sea water resistant. Halogen free. Colour jacket is petrol blue.
Dimension	: 4 x 0.25
Conductor material	: Copper, bare
Stranding element	: No
Conductor category	: Class 6 = very flexible
Core insulation material	: Copolymer, thermoplastic
Protective conductor	: No
Core identification	: Colour
Inner sheath	: Yes
Screen over stranding element	: None
Screen	: Yes
Screen over stranding	: Braiding
Model	: Round
Colour outer sheath	: Other
Material outer sheath	: Copolymer, thermoplastic
Flame retardant	: In accordance with EN 60332-1-2
Torsion resistant	: No
Halogen free (acc. EN 60754-1/2)	: Yes
Oil resistant (acc. EN 60811-404)	: Yes
Low smoke (acc. BS EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Outer diameter approx.	: 6.5mm
Permitted cable outer temperature during assembling/handling	: -25°C to 90°C
Permitted cable outer temperature after assembling without vibration	: -40°C to 90°C
Max. conductor temperature	: 70°C
Bending radius	: 49mm
Nominal voltage U0	: 300V
No. bending cycli	: 3000000



JOBARCO

Core protecton	: No
Nominal voltage U	: 300V
Conductor surface	: Bare
	: No
	: Round
Shape of conductor	: Round