

Signal-/telecommunications cable Inducom JPPDV-AF Dca



Application : Instrumentation cable for signalling and control applications in low-voltage installations.

TECHNICAL DATA : 0198676

Standards : NEN-EN 50288-7

Remarks : According to NEN standard: without communication core. Cores white and black in pairs. Numbered per pair (white 1, black 1 etc.).

Dimension : 1 x 2 x 1,3
 Conductor category : Class 2 = stranded
 Conductor material : Cu, bare
 Stranding : Layers
 Stranding element : Pairs
 Core insulation : XLPE (VPE)
 Core identification : Numbers
 Screen over stranding element : None
 Screen over stranding : Foil
 Longitudinal water blocking : No
 Radial water blocking : No
 Protective sheath : No
 Armouring : Yes
 Material outer sheath : PVC
 Colour outer sheath : Black
 Halogen free (acc. EN 60754-1/2) : No
 Flame retardant : In accordance with EN 60332-3-24
 Low smoke (acc. EN 61034-2) : No
 Circuit integrity : No
 Outer diameter approx. : 11.5mm
 Permitted cable outer temperature, in movement : -5°C to 50°C
 Permitted cable outer temperature, fixed : -30°C to 70°C
 Outdoor use permitted : Yes
 Euro fire class acc. to EN 13501-6 : Dca
 Euro class smoke generation : s3 (heavy smoke production)
 Euro class flaming droplets : d2 (flaming droplets/particles persisting > 10 s)
 Euro class acidity level : a3