

Flexible cable Werkplaatskabel JWPK



Application : A heavy-duty cable for use in industrial environment. Very good oil and media resistant. The cable is free of halogen.

TECHNICAL DATA : TYPE JWPK

Remarks : Very flexible even in case of low temperatures due to the polyurethane outer sheath. Also very good abrasion resistant.

Conductor category	: Class 5 = flexible
Conductor material	: Cu, bare
Core insulation	: Rubber (EPR)
Core identification	: Colour
Protective conductor	: Yes
Screen	: No
Material outer sheath	: PUR (Polyurethane)
Colour outer sheath	: Orange
Model	: Round
Halogen free (acc. EN 60754-1/2)	: Yes
Flame retardant	: No
Low smoke (acc. EN 61034-2)	: No
Oil resistant (acc. EN 60811-404)	: Yes
Max. conductor temperature	: 94°C
Permitted cable outer temperature, fixed	: -40°C to 85°C
Nominal voltage U ₀	: 450V
Nominal voltage U	: 750V

ProductNr	Dimension	Outer diameter approx. (mm)
0149203	3 x 1,5	9.3
0149204	4 x 1,5	10.3

ProductNr	Dimension	Outer diameter approx. (mm)
0149223	3 x 2,5	11.1
0149225	5 x 2,5	13.5