

Data and communication cable Jobcom ATEX-e RE-2X(ST)YSWBYfl



Application	: Instrumentation cable for signalling and control applications in low-voltage installations. Especially suited for ATEX EX-e applications. The cable complies to the standards as stated in the latest NEN standard.
TECHNICAL DATA	: TYPE RE-2X(ST)YSWBYfl
Standards	: NEN-EN 50288-7
Remarks	: According to NEN standard: without communication core. Cores white and black in pairs. Numbered per pair (white 1, black 1 etc.). UV resistant acc. to UL1581, s.1200. Oil resistant acc. to ICEA S-73-532. Capacitance c/c 1 pair: max. 100 nF/km; 2 pairs and more: max. 75 nF/km. Inductance at 1 kHz: max. 1 mH/km. Printing cable: JOBCOM EX Type 2.
Stranding element	: Pairs
Conductor material	: Copper, bare
Conductor category	: Class 2 = stranded
Core insulation material	: Crosslinked polyethylene (XLPE)
Core identification	: Numbers
Stranding	: Layers
Material outer sheath	: Polyvinyl chloride (PVC)
Screen over stranding element	: None
Screen over stranding	: Foil + braiding
Halogen free (acc. IEC 60754-2)	: No
Longitudinal water blocking	: No
Halogen free (acc. EN 60754-1/2)	: No
Radial water blocking	: No
Low smoke (acc. IEC 61034-2)	: No
Protective sheath	: No
Insulation integrity in accordance with IEC 60331	: No
Low smoke (acc. BS EN 61034-2)	: No
Armouring	: No
Oil resistant (acc. IEC 60811-404)	: No
Permitted cable outer temperature during assembling/handling	: -5°C to 70°C
Permitted cable outer temperature after assembling without vibration	: -30°C to 70°C
Flame retardant	: In accordance with EN 60332-3-24
Circuit integrity	: No
Outdoor use permitted	: Yes



UV resistant	: Yes
Armouring/reinforcement	: Braiding
Conductor surface	: Bare
	: No
Longitudinal water blocking cable	: No
Radial water blocking cable	: No
	: Steel
	: Round
Oil resistant (acc. EN 60811-404)	: No
Underground installation	: Yes
	: No
	: No
	: No
	: Yes

ProductNr	Dimension	Conductor Diameter (mm)	Colour outer sheath	Number of stranding elements	Outer diameter approx. (mm)
0195045	8 x 2 x 1.3	1.3	Blue	8	20.1
0195019	12 x 2 x 0.75	0.75	Black	12	20.8
0195046	12 x 2 x 1.3	1.3	Blue	12	25
0195048	16 x 2 x 1.3	1.3	Black	16	30.4
0195047	16 x 2 x 1.3	1.3	Blue	16	30.4