

Elevator cable Joblift LSTN



Application : Lift cable for trailing cable installation, drag chains and as controlcable in conveyor facilities, machine-tools.

TECHNICAL DATA : TYPE LSTN

Conductor material	: Cu, bare
Conductor category	: Class 6 = very flexible
Core insulation	: Rubber (EPR)
Protective conductor	: Yes
Suspension element	: Hemp
Screen	: No
Material outer sheath	: CR (polychloroprene)
Colour outer sheath	: Black
Model	: Round
Torsion resistant	: Yes
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: Yes
Permitted cable outer temperature, in movement	: -25°C to 80°C
Permitted cable outer temperature, fixed	: -40°C to 80°C
Nominal voltage U ₀	: 300V
Nominal voltage U	: 500V

ProductNr	Dimension	Outer diameter approx. (mm)
0133507	7 x 1	13
0133512	12 x 1	18.6
0133518	18 x 1	18.8
0133524	24 x 1	21.6

ProductNr	Dimension	Outer diameter approx. (mm)
0133607	7 x 1,5	14.1