



JOBARCO

Power cable < 1 kV, for flexible applications Laskabel H01N2-D



TECHNICAL DATA

	: TYPE H01N2-D
Standards	: DIN VDE 0282 deel 6.
Conductor material	: Copper, bare
Conductor category	: Class E = very flexible
Core insulation material	: Rubber
Core identification	: None
Model	: Round
Material outer sheath	: Rubber - polychloroprene (CR)
Flame retardant	: No
Halogen free (acc. EN 60754-1/2)	: No
Oil resistant (acc. EN 60811-404)	: No
Low smoke (acc. BS EN 61034-2)	: No
Permitted cable outer temperature during assembling/handling	: -25°C to 80°C
Permitted cable outer temperature after assembling without vibration	: -40°C to 80°C
Max. conductor temperature	: 80°C
Nominal voltage U ₀	: 100V
Nominal voltage U	: 100V
Conductor surface	: Bare
	: Round
Shape of conductor	: Round



ProductNr	Dimension	Colour outer sheath	Outer diameter approx. (mm)
0147049	1 x 16	Black	11
0147051	1 x 25	Black	12.7
0147055	1 x 35	Black	14.2
0147050	1 x 50	Black	16.5
0147094	1 x 70	Black	19.2
0147095	1 x 95	Black	21.4
0147098	1 x 95	Red	21.4
0147096	1 x 120	Black	24