

Power cable < 1 kV, for flexible applications Purflex PUR-PVC-CY



Application	: Flexible cable for extreme circumstances. Very good oil, hydrolysis and microbes resistant. Suitable for use in moist or damp environments.
TECHNICAL DATA	: TYPE PUR-PVC-CY
Remarks	: Outer sheath matt and low adhesive.
Conductor material	: Copper, bare
Stranding element	: No
Conductor category	: Class 5 = flexible
Core insulation material	: Polyvinyl chloride (PVC)
Core identification	: Numbers
Inner sheath	: No
Screen over stranding element	: None
Screen	: Yes
Screen over stranding	: Braiding
Model	: Round
Colour outer sheath	: Black
Material outer sheath	: Polyurethane (PUR)
Flame retardant	: No
Halogen free (acc. EN 60754-1/2)	: No
Oil resistant (acc. EN 60811-404)	: Yes
Low smoke (acc. BS EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Permitted cable outer temperature during assembling/handling	: -5°C to 70°C
Permitted cable outer temperature after assembling without vibration	: -40°C to 80°C
Max. conductor temperature	: 80°C
Nominal voltage U ₀	: 300V
Core protecton	: No
Nominal voltage U	: 500V
Conductor surface	: Bare
	: No
	: Round
Shape of conductor	: Round



JOBARCO

ProductNr	Dimension	Protective conductor	Outer diameter approx. (mm)	Bending radius (mm)
0152404	4 x 0.75	Yes	6.9	86
0152407	7 x 0.75	Yes	8.2	102
0152602	2 x 1.5	No	6.9	86
0152604	4 x 1.5	Yes	8.1	101