

Control cable UL LIYYCY-JZ



| | |
|---|--|
| Application | : Flexible cable, copper braided. Protects against electromagnetic interference. |
| TECHNICAL DATA | : TYPE LIYYCY-JZ |
| Standards | : UL 2587; CSA AWM IA/B IIA/B |
| Remarks | : Outer jacket colour=RAL7001. |
| Conductor category | : Class 5 = flexible |
| Stranding element | : No |
| Conductor material | : Cu, bare |
| Core insulation | : PVC |
| Core identification | : Numbers |
| Protective conductor | : Yes |
| Inner sheath | : Yes |
| Screen over stranding element | : None |
| Screen over stranding | : Braiding |
| Material outer sheath | : PVC |
| Colour outer sheath | : Grey |
| Halogen free (acc. EN 60754-1/2) | : No |
| Flame retardant | : In accordance with EN 60332-1-2 |
| Low smoke (acc. EN 61034-2) | : No |
| Low temperature resistant (acc. EN 60811-504+505+506) | : No |
| Oil resistant (acc. EN 60811-404) | : Yes |
| Permitted cable outer temperature, in movement | : -5°C to 90°C |
| Permitted cable outer temperature, fixed | : -40°C to 90°C |
| Nominal voltage U | : 600V |
| Core protecton | : No |

| ProductNr | Dimension | Outer diameter approx. (mm) | Bending radius (mm) |
|-----------|-----------|-----------------------------|---------------------|
|-----------|-----------|-----------------------------|---------------------|

| ProductNr | Dimension | Outer diameter approx. (mm) | Bending radius (mm) |
|-----------|-----------|-----------------------------------|------------------------|
| 1217804 | 4 x 4 | 15.3 | 91 |
| 1217904 | 4 x 6 | 16.8 | 100 |