



# JOBARCO

## Power cable < 1 kV, for fixed installations Kemaflex YKO



<b>Application</b>	<b>: Flexible installation cable, KEMA approved, low voltage, NEN 1010 areas, with steel wire braiding.</b>
<b>TECHNICAL DATA</b>	<b>: TYPE YKO</b>
Standards	: KEMA K176
<b>Remarks</b>	<b>: Unique, flexibel, installation cable in 1.5 and 2.5 mm<sup>2</sup></b>
Conductor material	: Copper, bare
Conductor category	: Class 5 = flexible
Core insulation material	: Polyvinyl chloride (PVC)
Core colour	: Several
Max. conductor temperature	: 77°C
Protective conductor	: No
Flame retardant	: In accordance with EN 60332-3-24
Screen	: Yes
Drain wire	: Yes
Suspension element	: None
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Protective barrier	: None
Oil resistant (acc. EN 60811-404)	: No
Lead sheath	: No
Armouring/reinforcement	: Braiding
Material outer sheath	: Polyvinyl chloride (PVC)
Permitted cable outer temperature after assembling without vibration	: -30°C to 70°C
Colour outer sheath	: Grey
Nominal voltage U	: 750V
Halogen free (acc. EN 60754-1/2)	: No
Low smoke (acc. BS EN 61034-2)	: No
Insulation integrity	: No
Permitted cable outer temperature during assembling/handling	: -5°C to 70°C
Nominal voltage U <sub>0</sub>	: 450V
Shape of conductor	: Round
Conductor surface	: Bare
Twisted cores	: No
Specification core insulation	: Other
	: Yes
Specification material outer sheath	: Other



# JOBARCO

Circuit integrity

- : Round
- : None
- : Yes
- : No
- : No
- : No
- : No



# JOBARCO

<b>ProductNr</b>	<b>Dimension</b>	<b>Number of cores</b>	<b>Core identification</b>	<b>Outer diameter approx. (mm)</b>	<b>(Ohm/km)</b>	<b>Min. permitted bending radius, stationary application/permanent installation (mm)</b>
0109604	4 x 1.5	4	Colour	15.6	13.3	234
0109612	12 x 1.5	12	Numbers	21.3	13.3	320
0109625	25 x 1.5	25	Numbers	27.9	13.3	419
0109702	2 x 2.5	2	Colour	15.2	8	228
0109703	3 x 2.5	3	Colour	16	8	240
0109704	4 x 2.5	4	Colour	17.5	8	263
0109707	7 x 2.5	7	Numbers	19.3	8	290
0109712	12 x 2.5	12	Numbers	23.8	8	357