

Signal-/telecommunications cable Jobsignal YY-ST Dca



Application : Signal and control cable for use in intercom, telephone and security appliances.

TECHNICAL DATA : TYPE YY-ST Dca

Standards : KEMA K 102-314, CPR

Remarks : Colour code according to NEN1597. Drain wire 0.8mm underneath foil. Outer jacket PVCmb.

Conductor category	: Class 1 = solid
Conductor material	: Cu, bare
Stranding	: Layers
Stranding element	: Pairs
Core insulation	: PVC
Core identification	: Colour
Screen over stranding element	: None
Screen over stranding	: Foil
Longitudinal water blocking	: No
Radial water blocking	: No
Armouring	: No
Material outer sheath	: PVC
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Permitted cable outer temperature, in movement	: -20°C to 70°C
Permitted cable outer temperature, fixed	: -20°C to 70°C
Outdoor use permitted	: No
Euro fire class acc. to EN 13501-6	: Dca
Euro class smoke generation	: s3 (heavy smoke production)
Euro class flaming droplets	: d2 (flaming droplets/particles persisting > 10 s)
Euro class acidity level	: a3

ProductNr	Dimension	Colour outer sheath	Outer diameter approx. (mm)
0157602	1 x 2 x 0,8	Grey	4.8
0157652	1 x 2 x 0,8	Red	4.8
0157604	2 x 2 x 0,8	Grey	6.8
0157654	2 x 2 x 0,8	Red	6.8
0157606	3 x 2 x 0,8	Grey	7.4
0157658	2 x 4 x 0,8	Red	7.8
0157608	4 x 2 x 0,8	Grey	7.8
0157610	5 x 2 x 0,8	Grey	8.8
0157667	6 x 2 x 0,8	Blue	9.2
0157612	6 x 2 x 0,8	Grey	9.2
0157616	8 x 2 x 0,8	Grey	10.1
0157624	12 x 2 x 0,8	Grey	11.8
0157648	24 x 2 x 0,8	Grey	16.6