

UL - STYLE TABEL

Style	Temp. °C	Materiaal	Voltage	AWG
<u>Enkeladerig:</u>				
1007	80	PVC	300	32 - 16
1011	80	PVC	600	28 - 3
1015	105	PVC	600	28 - 9
1148	60	PVC	600	26 - 16
1149	60	PVC	600	26 - 16
1160	60	PVC	300	26 - 16
1162	60	PVC	600	8
1207	90	PVC	600	28
1498	80	PVC	600	26 - 9
1499	90	PVC	600	26 - 9
1729	80	PVC	300	26 - 16
10012	80/90/105	PVC	0,6/1 kV	30 - 3
10042	80	TPE-E	300	26 - 2
10053	80	PVC	300	26 - 10
10108	90	TPE-E	300	26 - 10
10258	90	TPE-E	0,6/1 kV	26 - 2
10467	80	PP	300	36 - 16
10479	90	TPE-E	300	32 - 10
10615	80	FRPE	600	26 - 3

Meeraderig:

2448	60	PVC	30	min. 40
2463	80	PVC	600	min. 40
2464	80	PVC	300	*
2490	60	PVC	*	min. 36
2493	60	PVC	*	30 - 16
2550	90	PVC	600	min. 40
2570	80	PVC	600	min. 40
2587	90	PVC	600	min. 40
2653	90	PVC	600	min. 44
20195	75	PVC	300/500	0,75 – 4 mm ²
20234	80	PUR	0,6/1 kV	26 - 2
20235	80	PUR	*	min. 36
20403	60	PVC	300	28 - 16
20870	80	PUR	300	*
20911	80	PUR	300	min. 36
21387	90	TPE	1 kV	min. 26
21529	90	TPE	300	min. 26
21530	90	TPE	600	min. 26

* = niet gespecificeerd



- **ADRES** Verbreepark 15 NL-2731 BR Benthuizen • **TELEFOON** +31 79 331 93 13 • **FAX** +31 79 342 35 72
- **E-MAIL** info@jobarco.com • **INTERNET** www.jobarco.com
- **BANK** ABN AMRO Bank N.V. 50.32.83.169 • **IBAN** NL35ABNA0503283169 • **BIC** ABNANL2A
- **BTW** NL001714983B01 • **KvK** 28058530 • **EORI** NL001714983

